

J-FLEX MATERIAL DATA SHEET

ELECTRICALLY CONDUCTIVE SILICONE SHEET



Description

Electrically Conductive Grade Silicone is designed to be used in many different applications. It is a carbon filled silicone material that will act as a low amperage conductor and also provides protection against electrostatic discharge.

This material is available in Standard Rolls 500mm wide x 10 metre long.

Thickness range:- 0.2mm, 0.5mm, 0.8mm, 1.0mm, 1.5mm, 2mm, 2.5mm & 3.0mm

PHYSICAL PROPERTIES	Units	Values
Tear Strength	KN/m	12
Compression set (24hrs @ 100°C)	%	8
Hardness	Shore A	75°
Density	g/cm ³	1.22
Tensile Strength	MPa	6
Volume Resistivity	Ω•cm	4.3
Elongation	%	150
Temperature	°C	-50 to +240
Appearance	Black colour, smooth surface both sides	

The above values are typical properties and are provided for information only. They should not be used to set specification requirements. It is up to the end user to determine whether the material is suitable for the intended application.

June 2013



J-FLEX RUBBER PRODUCTS
Engineering Rubber Components & Specialised Sheeting Products

Units 1 & 2, London Road Business Park, Retford,
Nottinghamshire, DN22 6HG, United Kingdom
tel: +44 (0) 1777 712 400 fax: +44 (0) 1777 712 409
www.j-flex.co.uk

